

ECO CUSHION PLUS®

Eco-Cushion Plus carpet cushion makes a positive impact on the earth's environment while providing the true luxury and comfort that a quality cushion provides. Inexpensive carpets need Eco-cushion Plus. Expensive carpets deserve it.

The Affordable Green Choice

- Recycled content from auto tires extends the life of the carpet
- Contributes to LEED® green building credits for recycled content, regional materials and low-emitting materials
- High performance backing contains materials from responsible reforestation program
- 100% natural treatment to prevent the growth of mold, mildew and fungus

Healthy Home

- Carpet and Rug Institute Green Label approved for indoor air quality
- Contains Ultra-Fresh®, non-allergenic, anti-microbial
- Contains baking soda for added deodorizing protection
- Open cell rubber for air circulation to improve maintenance
- Noise reduction

Quality Assurance

- High density construction for superior carpet performance and comfort underfoot
- Superior performance backing for strength, durability and quality installation
- Can be installed above or below grade and over radiant heat
- Will not cause carpet to stretch and buckle

Warranty

Guaranteed for the useful life of the original carpet when installed wall to wall.

For information or to place an order please contact:

Fabricushion Ltd. T: 800 475 0801
 259 Steelcase Road West 905 475 0801
 Markham, ON F: 905 475 0823
 Canada E: customerservice@fabricushion.com
 L3R 2P6 W: www.fabricushion.com

Member of CMCC (Canadian Manufacturers of Carpet Cushion)
 Member of CCC (Carpet Cushion Council)

Fabricushion Ltd. is a member of The Stewart Group of Companies
www.stewartgroup.com

Specifications

Green Approved	Green Label Approved by CRI (Carpet and Rug Institute) Indoor Air Quality Testing Program
Application	Heavy Residential / Moderate Commercial
Uses	Wall-to-wall carpet Area rugs
Installations	Conventional installation Above and below grade Over radiant floors
Anti-microbial	Ultra-Fresh
Hypo-allergenic	Yes
Baking Soda	Yes
R-Value	0.68 / ASTM C518
Flame Retardant	Passes Pill Test
CMHC	Approved
Type	Recycled tires
Content	100% virgin SBR synthetic rubber with recycled tire crumb
Backing	High performance / TEXTRON
Thickness	8 mm (0.310")
Density	288 kg / m ³ (18 lbs / ft ³)
Roll Width	1.8 m (72" 6 ft)
Roll Size	12.5 m ² (15 yd ² 135 ft ²)
Roll Weight	29 kgs (64 lbs)
Colour	Green
Weight	2.3 kg / m ² (68 oz / yd ²)
CGSB Specification	20-GP-23a Type 2

